Safety Data Sheet dated 2/9/2015, version 1





SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name:

FLUORESCENTE SPRAY

Trade code:

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Spray painting decorative household, industrial and professional

1.3. Details of the supplier of the safety data sheet Company: KENDA FARBEN S.R.L.

Company:

VIA DELLA RESISTENZA 1/2

27032 FERRERA ERBOGNONE PV

TEL. 0382 998902 FAX. 0382 998297

Competent person responsible for the safety data sheet:

1.4. Emergency telephone number

Centro Antiveleni - Ospedale di Niguarda - Milano - Tel. 0039 02 66101029

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Directive criteria, 67/548/CE, 99/45/EC and following amendments thereof:

Properties / Symbols:

F+ Extremely flammable

Xi Irritant

R Phrases:

R12 Extremely flammable.

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

EC regulation criteria 1272/2008 (CLP):

- Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.
- Warning, Eye Irrit. 2, Causes serious eye irritation.
- Warning, STOT SE 3, May cause drowsiness or dizziness.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Symbols:





Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H319 Causes serious eve irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P405 Store locked up.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Contents:

methyl acetate

acetone; propan-2-one; propanone

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

>= 25% - < 30% methyl acetate

REACH No.: 01-2119459211-47-XXXX, Index number: 607-021-00-X, CAS: 79-20-9, EC: 201-185-2

F,Xi; R11-36-66-67

2.6/2 Flam. Liq. 2 H225

3.3/2 Eye Irrit. 2 H319

3.8/3 STOT SE 3 H336

>= 15% - < 20% propane

60.000/1

Page n. 2 of 11

Index number: 601-003-00-5, CAS: 74-98-6, EC: 200-827-9 F+; R12; substance with a Community workplace exposure limit 2.2/1 Flam. Gas 1 H220

>= 7% - < 10% butane

Index number: 601-004-00-0, CAS: 106-97-8, EC: 203-448-7 F+; R12; substance with a Community workplace exposure limit 2.3/3 Aerosols 3 H229

2.2/1 Flam. Gas 1 H220

>= 7% - < 10% o-xylene

Index number: 601-022-00-9, CAS: 1330-20-7, EC: 215-535-7

Xn,Xi; R10-20/21-38

- 2.6/3 Flam. Liq. 3 H226
- 3.1/4/Dermal Acute Tox. 4 H312
- 3.1/4/Inhal Acute Tox. 4 H332
- 3.2/2 Skin Irrit. 2 H315

>= 7% - < 10% acetone; propan-2-one; propanone

REACH No.: 01-2119472426-35-XXXX, Index number: 606-001-00-8, CAS: 67-64-1, EC: 200-662-2

F,Xi; R11-36-66-67

- 2.6/2 Flam. Liq. 2 H225
- 3.3/2 Eye Irrit. 2 H319
- 3.8/3 STOT SE 3 H336

>= 5% - < 7% n-butyl acetate

Index number: 607-025-00-1, CAS: 123-86-4, EC: 204-658-1 R10-66-67; substance with a Community workplace exposure limit

- **3** 2.6/3 Flam. Liq. 3 H226
- 3.8/3 STOT SE 3 H335

>= 3% - < 5% butane

Index number: 601-004-00-0, CAS: 75-28-5, EC: 200-857-2 F+; R12; substance with a Community workplace exposure limit

2.2/1 Flam. Gas 1 H220

>= 1% - < 3% methanol

REACH No.: 01-2119433307-44-XXXX, Index number: 603-001-00-X, CAS: 67-56-1, EC: 200-659-6

F,T; R11-23/24/25-39/23/24/25

2.6/2 Flam. Liq. 2 H225

3.1/3/Dermal Acute Tox. 3 H311

3.1/3/Inhal Acute Tox. 3 H331

3.1/3/Oral Acute Tox. 3 H301

3.8/1 STOT SE 1 H370

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use vaporized water or foam.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methyl acetate - CAS: 79-20-9

ACGIH, 200 ppm, 250 ppm - Notes: Headache, dizziness, nausea, eye dam (degeneration of ganglion cells in the retina)

propane - CAS: 74-98-6

TLV TWA - 1000 ppm - 0 mg/m3

VLE short - 1000 ppm

butane - CAS: 106-97-8 ACGIH, 1000 ppm - Notes: CNS impair o-xylene - CAS: 1330-20-7 EU - LTE(8h): 221 mg/m3, 50 ppm - STE: 442 mg/m3, 100 ppm - Notes: Bold-type; Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography) ACGIH, 100 ppm, 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair acetone; propan-2-one; propanone - CAS: 67-64-1 EU - LTE(8h): 1210 mg/m3, 500 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography) ACGIH, 500 ppm, 750 ppm - Notes: (A4), BEI - (URT and eye irr, CNS impair, hematologic eff) n-butyl acetate - CAS: 123-86-4 ACGIH, 150 ppm, 200 ppm - Notes: Eye and URT irr butane - CAS: 75-28-5 ACGIH, 1000 ppm - Notes: CNS impair VLE short - 1000 ppm methanol - CAS: 67-56-1 EU - LTE(8h): 260 mg/m3, 200 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

DNEL Exposure Limit Values

nausea

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

ACGIH, 200 ppm, 250 ppm - Notes: Skin BEI - Headache, eye dam, dizziness,

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

Environmental exposure controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance and colour:

Liquid aspect (under pressure), various colours.

Odour:

Caracteristic of solvent

Odour threshold:

N.A. N.A.

Melting point / freezing point:

N.A.

Initial boiling point and boiling range: N.A.

Solid/gas flammability: Extremely flammable Upper/lower flammability or explosive limits:

Vapour density:

N.A.

Flash point:

Inf. 0 ° C

Evaporation rate:

N.A.

Vapour pressure:

a 20°C - 4,0 bar

Relative density:

a 50°C - 8,0 bar

Solubility in water:

0,75 - 0,80 g/ml

Solubility in oil:

NO SI

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: Decomposition temperature: N.A. N.A.

Viscosity:

N.A.

Explosive properties:

N.A.

Oxidizing properties:

N.A.

9.2. Other information

Miscibility:

N.A.

Fat Solubility: Conductivity:

N.A. N.A.

Substance Groups relevant properties N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

methyl acetate - CAS: 79-20-9

LD50 (RABBIT) ORAL: 3705 MG/KG

o-xylene - CAS: 1330-20-7

LD50 (RAT) ORAL: 5000 MG/KG

acetone; propan-2-one; propanone - CAS: 67-64-1

LD50 (RABBIT) ORAL: 5300 MG/KG

methanol - CAS: 67-56-1

LD50 (RAT) ORAL SINGLE DOSE: 5628 MG/KG

LD50 (RABBIT) SKINSINGLE DOSE: 15800 MG/KG

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

N.A.

12.2. Persistence and degradability

None

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

ADR-UN number:

1950 1950

IATA-Un number: IMDG-Un number:

1950

14.2. UN proper shipping name

ADR-Shipping Name:

AEROSOL

IATA-Technical name:

AEROSOL

IMDG-Technical name:

AEROSOL

N.A.

14.3. Transport hazard class(es)

ADR-Class:

2 5F

ADR-Label:

_

```
ADR - Hazard identification number: -
      IATA-Class:
                                    2.1
      IATA-Label:
                                    2.1
      IMDG-Class:
                                    2
      N.A.
14.4. Packing group
      ADR-Packing Group:
      IATA-Packing group:
     IMDG-Packing group:
     N.A.
14.5. Environmental hazards
     Marine pollutant:
                                   Severe marine pollutant
     N.A.
14.6. Special precautions for user
     ADR-Tunnel Restriction Code: -
     IATA-Passenger Aircraft:
     IATA-Cargo Aircraft:
                                   203
     IMDG-Technical name:
                                   AEROSOL
     IMDG-Page:
                                   F-D, S-U
     IMDG-EMS:
                                   F-D, S-U
     IMDG-MFAG:
     N.A.
14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
```

```
SECTION 15: Regulatory information
      15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
            Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)
            Dir. 99/45/EC (Classification, packaging and labelling of dangerous preparations)
            Dir. 98/24/EC (Risks related to chemical agents at work)
            Dir. 2000/39/EC (Occupational exposure limit values)
            Dir. 2006/8/EC
            Regulation (EC) n. 1907/2006 (REACH)
            Regulation (EC) n. 1272/2008 (CLP)
            Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
            Regulation (EU) n. 453/2010 (Annex I)
            Regulation (EU) n. 286/2011 (ATP 2 CLP)
            Regulation (EU) n. 618/2012 (ATP 3 CLP)
            Regulation (EU) n. 487/2013 (ATP 4 CLP)
            Regulation (EU) n. 944/2013 (ATP 5 CLP)
```

Regulation (EU) n. 605/2014 (ATP 6 CLP) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

```
Volatile Organic compounds - VOCs = 630.53 g/l
```

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 0.00

Where applicable, refer to the following regulatory provisions:

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II):

N.A.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Text of phrases referred to under heading 3:

R10 Flammable.

R11 Highly flammable.

R12 Extremely flammable.

R20/21 Harmful by inhalation and in contact with skin.

R23/24/25 Toxic by inhalation,in contact with skin and if swallowed.

R36 Irritating to eyes.

R38 Irritating to skin.

R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H220 Extremely flammable gas.

H229 Pressurized container: may burst if heated.

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H301 Toxic if swallowed.

H370 Causes damage to organs.

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU. This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van

Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:

European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LTE: Long-term exposure.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STE: Short-term exposure.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day.

(ACGIH Standard).

WGK: German Water Hazard Class.